# Subpart B: Hazard Assessment


[§§ 68.20-68.42]



## Worse Case & Alternative Release Scenarios

Predicting Impact to the Community –
Hazard Assessment


Primary Causes of Accidents





#### **Hazard Assessment**

- RMP Requirements:
  - Offsite ConsequenceAnalysis
    - Worse-Case Scenario
    - Alternative Scenario
      - Requires
        consideration of
        Failure scenarios
        identified under
        68.50 or § 68.67
  - 5-year accident history





#### Offsite Consequence Parameters



- Offsite consequence analysis must include:
  - Toxic end points
  - Flammables
    - Overpressure, Radiant heat, Concentration – lower flammability limit
  - Also consider:
    - Wind speed, stability class, ambient temp, height of release, and topography, Liquid or gas release
    - Passive Mitigation
      - Release within an enclosure.

## **Effectiveness of Building Mitigation for Alternative Release Scenarios**





#### **Scenarios**

- RMPs are required to submit two different types of chemical release scenarios:
  - Worse Case
    - Largest vessel releases at one time
  - Alternative Case
    - More realistic release, usually smaller release over longer period of time

#### **Worse-Case Scenarios**

- Program 1 Facilities:
  - One worse-case scenario for each Program 1 process
- Program 2 and 3 Facilities:
  - One worse-case scenario for all toxics
  - One worse-case scenario for flammables
  - Additional worse-case scenario if different public receptors

#### **Alternative Release Scenario**

- All Program Facilities must:
  - One release scenario for each toxic substance
  - One release scenario for each flammable substance
- Must select a release that is:
  - More likely to occur than worse-case scenario
  - Will reach an offsite impact
  - Consider releases from transfer hoses, piping, pumps, overfilling, spills, or punctures

#### **Review and Documentation**




- Offsite consequence analysis must be reviewed every five years, or
- Within six months of any process change that could increase or decrease the distance to the end point

## Calculating Release Scenarios

- EPA provides a couple of methods to calculate release scenarios:
  - RMP \*Comp Computer software, easy to use, need basic data parameters (volume, size of container)
  - EPA tables Found in industry specific
     EPA guidance documents
  - Other Models Such as Areal Locations of Hazardous Atmospheres (ALOHA®)

#### **Distance To End Points**



Air dispersion modeling could be used for environmental planning

### Release Scenario Analysis

 Since a "zone of concern" can be developed for a given facility based on specific hazardous substances of concern, offsite consequences analyzes can be used to aid in community planning

#### **Worse Case Scenarios**





## Five-year accident history

- An Accident is Reportable . . . if the release:
  - Onsite Deaths, injuries or property damage.
  - [Known] Offsite Deaths, injuries, property damage, or environmental damage, evacuations, or sheltering-in-place.
- Requires corrections to the RMP within 6 months. {§ 68.195 Required Corrections}
  - Includes data required under §§ 68.168,
     68.170(j) [Prgm 2], and 68.175(l) [Prgm 3]